

## **A virtual network of ground-based microwave radiometers for monitoring of atmospheric stability and its potential impact in synergy with hyperspectral satellite observations.**

*Presenter: Maria Toporov, University of Cologne*

*Authors: Maria Toporov, Ulrich Löhnert*

Short-term forecasts of current high-resolution numerical weather prediction models still have large deficits in forecasting the exact temporal and spatial location of severe, locally influenced weather such as summer-time convective storms or cool season lifted stratus or ground fog. The thermodynamic instability - especially in the boundary layer - plays an essential role in the evolution of weather events. One way to assess the atmospheric instability offer so-called forecast or stability indices (STI). The temporal and spatial resolution of radiosonde soundings, which are traditionally used for calculation of STI, is not sufficient to capture the initiation and the development of convection. Ground-based remote sensing instruments and instruments on board of geostationary satellites provide high temporally resolved information on vertical structure of the atmosphere and can be used for monitoring of atmospheric stability.

Previous studies showed that microwave profilers (MWR) are well suited for continuously monitoring the temporal development of atmospheric stability (Cimini et al. 2015). However, the vertical resolution of microwave temperature and humidity profiles is best in the lowest kilometer above the surface, decreasing rapidly with increasing height. Typical stability indices (STI) used to assess the potential of convection rely on temperature and humidity values not only in the region of the boundary layer but also in the layers above. Therefore, satellite remote sensing is expected to complement ground-based MWR and DIAL observations.

In this contribution, we present a neural network retrieval of stability indices, integrated water vapor (IWV) and liquid water path (LWP) from simulated satellite- and ground-based measurements based on the COSMO-REA2 reanalysis as truth. In order to make the approach feasible for data assimilation applications, we simulate satellite observations with the standard RTTOV model and use the RTTOV-gb (ground-based) for the ground-based microwave radiometers (De Angelis et al., 2016). Focusing on the temporal resolution and spatial coverage, the satellite-based instruments considered in the study are the currently operational SEVIRI and the future IRS, both in geostationary orbit. We show the single instrument performance and the synergy benefit in terms of correlation, uncertainty reduction, probability of detection and other forecast skill scores.

The hyperspectral geostationary IRS observations contain significantly more information on vertical humidity and temperature needed for assessment of atmospheric stability than SEVIRI measurements. Thus, the error of STI retrieved from simulated IRS observations was shown to decrease by up to 50% compared to SEVIRI. The additional ground-based MWR/DIAL measurements provide valuable improvements not only in the presence of clouds, which represent a limiting factor for infrared SEVIRI/IRS, but also under clear sky conditions.

To assess the spatial representativeness of observations of a single ground-based MWR and to estimate the required network density the retrieval is applied to a 150\*150km reanalysis domain. The impact of an additional ground-based network was investigated in two ways. First, CAPE/LI fields retrieved from satellite observations were merged with the CAPE/LI values from ground-based network by taking into account the corresponding error covariance matrices of both retrievals (statistical interpolation). Within this method the contribution of ground-based network consisting of varying number of radiometers (from one to 25) was shown to be significant under cloudy conditions. Second, by assuming the persistence of CAPE/LI field for a time period of three hours the last was taken as a first guess and updated with the CAPE/LI field obtained from satellite and/or ground-based observations. Within this method, the added value of ground-based observations, if compared to satellite contribution, is highly dependent on the current weather situation, cloudiness and the position of ground-based instruments.